

SPECIFICATIONS

L.O.A* : 9.75 m
Length of hull : 8.50 m
Width of hull : 3.30 m
Weight : 4 500 kg
Draft : 0.85 m
Minimum air draught on sea : 2.60 m
Fuel tank capacity : 550 l
Water tank capacity : 200 l
Engine : single or twin-engined single
Maximum engine power single engine : 440 HP
Maximum engine power twin-engined : 2 x 225 HP
Transmission : propeller shaft
EC certification : B8 / C10
Architects : Joubert-Nivelt
Designer : Olivier Flahaut

* with swimming platform and bow-fishing gangway options

STANDARD EQUIPMENT

Construction

Hull and deck reinforced polyester laminate
Wooden bulwark rail and rubbing strakes
Superstructure : cellular sandwich
Hull bottom : balsa sandwich
Deck : 12 mm marine ply sandwich
Stainless steel keel strip

Deck facilities

Walkaround deck layout
Self-draining chain locker
Stem-head anchor roller
2 fairleads forward and aft
2 mooring cleats fore and aft
7 handrails on coachroof and wheelhouse
Stainless bow pulpit
2 dorade cabin ventilators
Recessed fuel filler

Engine facilities

Diesel engine, prop shaft drive with protected propeller
Soundproofed engine compartment
550-litre fuel tank

Cockpit & deck

Self-draining cockpit
Transom door
3 folding slatted benches
1 engine casing
1 aft cockpit locker converts to live fish well (option)
1 stern locker (access to hydraulic steering ram)

1 emergency tiller
2 rod-holders
Eyelets for fenders
Manual bilge pump
Bathing ladder

Wheelhouse

14 safety-glass windows, one opening
1 sliding side door
1 sliding aft door
Instrument console
Steering compass
1 electric windscreen wiper
1 hydraulic steering wheel
Engine controls
Helmsman's seat
Pivoting seat for 2 co-pilots
Chart table with stowage
Bi-fold doors for forward cabin
Floor hatch to bilge locker
1 engine casing
U-shaped dinette converting into double berth
Adjustable (height) dinette table
Opening port in head
3 handrails

Galley

Sink with pressurized water
2-burner cooker + oven
200-litre fresh-water tank
85-litre refrigerator
Cupboards, drawers and shelves
Bottle storage

Forward cabin

V-shaped double berth
Lockers below berth
Opening hatch
2 portholes
Hanging space - Cubby - holes for stowage

Head

Shower/wash-basin/
Sea toilet with holding tank
Opening port in head

Electrical facilities

1 x 12 volt, 105 amp battery per engine
2 x 12 volt, 105 amp battery for services
Control panel with engine battery isolator
Cabin, head and wheelhouse lighting
Navigation lights
Bilge pump